



Product Service

# Attestation of Conformity

No. N8 15 08 85387 014

**Holder of Certificate: DKM Motor Co., Ltd.**4F., Incheon Techpia Na-Bldg., Geobuk-ro 17  
Seo-gu, Incheon 404-825  
REPUBLIC OF KOREA**Product: Motor, drive-  
(ELECTROMAGNETIC BRAKE MOTOR)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2006/95/EC relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

**Test report no.:** CPSA01286815**Date,** 2015-08-21  
(Hyuk-Jun Kwon)

**CE** After preparation of the necessary technical documentation as well as the EC conformity declaration the required CE marking can be affixed on the product. Other relevant directives have to be observed.

Page 1 of 3



Product Service

**Attestation of Conformity**  
**No. N8 15 08 85387 014**

**Model(s):** 9BD\*K-200\*\*\_\*\* \*\*, 9BD\*K-150\*\*\_\*\* \*\*, 9BD\*K-120\*\*\_\*\* \*\*,  
9BD\*K-90\*\*\_\*\* \*\*, 9BD\*K-60\*\*\_\*\* \*\*, 9BD\*K-40\*\*\_\*\* \*\*,  
8BD\*K-25\*\*\_\*\* \*\*  
(see attachment for model description)

**Parameters:**

Rated input voltage:	380/400 V a.c.
Rated frequency:	50/60 Hz
Rated input power:	200W; 0.74/0.66A, 0.81/0.69A, 150W; 0.53/0.48A, 0.57/0.50A, 120W; 0.50/0.41A, 0.49/0.43A, 90W; 0.35/0.33A, 0.37/0.35A, 60W; 0.31/0.28A, 0.34/0.30A, 40W; 0.19/0.18A, 0.20/0.19A, 25W; 0.14/0.13A, 0.15/0.14A
Protection class:	I
Degree of protection against ingress of liquids:	IP20-IP54

**Tested according to:** EN 60034-1:2010



## Attachment to the Certification

No. N8 15 08 85387

### Model description

9BD\*K-200\*\*\_\*\* \*\*

1st "\*" means motor shaft shape can be G, S, D or K.

2nd "\*" means fan type can be F, F2 or blank.

3rd "\*" means attaching gearhead can be G, P, H, W, WH or blank.

4th "\*" means pole can be A or blank.

5th "\*" means connection type can be T or blank.

6,7th "\*\*\*" mean client option for shaft change can be any number or blank.